


Internal mold: DYHDMI-002-I
External mold: DYHDMI-002-0



Pin Assignment

P1		P2	P1		P2
1	White	1	10	White	10
3	Green	3	12	Green	12
5	Drain	5	8	Drain	8
4	White	4	19	White	19
6	Green	6	15	Green	15
2	Drain	2	17	Drain	17
7	White	7	13	Red	13
9	Green	9	14	Yellow	14
11	Drain	11	16	Orange	16
			18	White	18
			Shell	Drain Wire	Shell

ELECTRICAL TEST:

TEST CONDITION:

- CONDUCTION RESISTANCE: 5 Ω Max;
- INSULATION RESISTANCE: 10M Ω (Min)
- TEST VOLTAGE: DC 300V/0.01SEC
- 4K*2K*60HZ

Packaging requirements:

- Online flagging
- Heat sealing of ordinary PE bag
- Carton box: 39*33*26



4	MOIDING	PVC 45P WHITE	14	G	CUSTOMER		TITLE	HDMI AM TO AM CABLE WHITE
3	MOIDING	LD-PE	8	G	SHEET	1/1	CUST P/N	NICOC-HDMI-4-005NWT
2	CONNECTOR	HDMI A Type Plug, Insulator Black Gold Plated, Contact Gold Plated	2	PCS	REV	A/0	APPD	DATE:
1	CABLE	30AWG{(1/0.254CCS+FPE)*1P+D(1/0.254+HDPE)+FAM}*5P+1/0.254CCS*4C+AL+D(1/0.254CCS)+B(64*0.12ALM) WHITE PVC OD:6.0mm Printing Black	500	MM	UNITS:		CHRK	DATE:
NO.	ITEM	DESCRIPTION	Q' TY	UNIT	MM (INCH)		DR	DATE: