





Wiring Diagram

P1		P2	
1		1	white
2		2	orange
3		3	white
6		6	green
4		4	blue
5		5	white
7		7	white
8		8	brown

Remarks:
1. 100% open circuit short circuit&displacement test
2. Fluke channel test Pass.
   TEST LIMIT: ISO11801 Channel Class E
3. ROHS 2.0 and REACH COMPLIANT

No.	Mat.Name	Description
c	Cable	U/UTP CAT6 PATCH CABLE AWG32/7 (7/0.08 ± 0.008/BC) * 4P LSZH, OD 3.4 ± 0.2 MM
b	Overmold	PVC MOLDING
a	Connector	RJ45 8P8C,Gold plated pin contact 3u"

TECHly® PROFESSIONAL

RJ45 M TO RJ45 M CAT6 U/UTP 32AWG LSZH
P/N: ICOC U6-SLIM-0025BK2 - Art.: 366716 - L = 0,25 m
P/N: ICOC U6-SLIM-005BK2 - Art.: 366723 - L = 0,5 m
P/N: ICOC U6-SLIM-010BK2 - Art.: 366730 - L = 1 m
P/N: ICOC U6-SLIM-015BK2 - Art.: 366754 - L = 2 m
P/N: ICOC U6-SLIM-030BK2 - Art.: 366761 - L = 3 m
P/N: ICOC U6-SLIM-050BK2 - Art.: 366778 - L = 5 m
P/N: ICOC U6-SLIM-100BK2 - Art.: 366785 - L = 10 m